

# WATER METERS-MIXERS

## DS AND DM RANGE

- IP55 classified tight box, to be set on a wall (fixing screws provided)
- Digital display in litres of the desired volume of water, with countdown during flow automatic shut-down. Permanent memory of the pre-set volume of water.
- Relay output provided for pump control
- Flow hose towards mixer and elbow provided
- ON and OFF palm button
- On the water meter, cold water inlet with standardised connection
- On the water meter and mixer, cold and hot water inlet with standardised connection. Programming on the front face of the water temperature.
- Digital display at any time of the setpoint



## TECHNICAL DATA

### DOSEUR SIMPLE DS



#### TECHNICAL DATA

Measurement function	yes
Mixing function	no
Pump control outlet	yes
Cold water inlet	yes
Hot water inlet	no
Required water pressure	1 to 5 bars
Programming	from 0,1 to 999,9 litres
Capacity	from 15 to 40 litres/min

#### DIMENSIONS (mm) & WEIGHT (kg)

Length x Depth	L 400 x P 100
Height	H 200
Net weight	4 KG
Unions	3/4 - 20/27
Voltage	220-240 ~1PH+N+T
Frequency	50 HZ

### DOSEUR MÉLANGEUR DM



#### TECHNICAL DATA

Measurement function	yes
Mixing function	yes
Pump control outlet	yes
Cold water inlet	yes
Hot water inlet	yes
Required water pressure	1 to 5 bars
Programming	from 0,1 to 999,9 litres
Capacity	from 15 to 40 litres/min
Adjustment	Manual thermostatic expansion valve
Temp.	+2° to 50° C

#### DIMENSIONS (mm) & WEIGHT (kg)

Length x Depth	L 400 x P 100
Height	H 200
Net weight	4 KG
Unions	3/4 - 20/27
Voltage	220-240 ~1PH+N+T
Frequency	50 HZ

### MANUAL METER



#### TECHNICAL DATA

Body	in brass
Mounting	horizontal
Unions	2 x 1/2 M - 15/21 M
Range	from 0 to 100 litres