

# BLUE ROCK

## REFRIGERATED WORKTABLES



MADE IN FRANCE



We provide quality,  
professional equipment  
and services to artisan bakeries.



A chef in a white uniform is working with dough on a stainless steel table. The chef's hands are visible, and they are using a red-handled tool to shape the dough. The background is slightly blurred, showing the chef's uniform and the table surface.

# BLUE ROCK RANGE

The Blue Rock range of static cold Refrigerated Tables is designed for positive storage (+2°C to +15°C) of all pastry and viennese products.

Available with 2 to 6 doors and in a range of different finishes, they are equipped to accommodate all 400x600 mm trays or grids (400 entry direction).

## KNOW-HOW

**More than 40  
years by your side**

With more than 40 years of experience, CFI has reached its high level of expertise thanks to a unique know-how in the conception of cold equipments for bakeries and pastry shops, and a development of Made in France products, always more reliable and efficient.

VISIT

[WWW.FROID-CFI.FR](http://WWW.FROID-CFI.FR)

## LAB

**Discover your future  
equipment**

As a demonstration and training center, our LAB' is at your disposal to test our equipment in real-life situations. Our Baker Demonstrator is there to advise and assist you.

MAKE AN APPOINTMENT WITH US

**+33 (04) 75 57 55 00**

## ASSISTANCE

**At your service**

Benefit from the power of a worldwide network of distributors! We provide local support to bakers all over the world, to help you at every stage of your project.

CALL US

**+33 (04) 75 57 55 00**



# REFRIGERATED WORKTABLES BLUE ROCK RANGE

BLUE ROCK are dismountable refrigerated worktables with static positive cooling (+2°C to +15°C), designed to accommodate 400x600mm trays or grids (400 entry).

They ensure optimum preservation of finished pastry products and raw materials, thanks to their excellent hygiene conditions and precise temperature control.

They are available in 2 to 6-door versions, with either a built-in group (GL) - except for the 6-door version - or a remote group (GD).



## THE RANGE

BLUE ROCK is the ideal solution for all bakeries, thanks to its **great sturdiness and ability to adapt to all laboratory configurations**.

They are available in **2, 3, 4, 5 and 6-door** versions, as well as in **stainless steel (304 int./ 430 ext.) or white PVC** panels.

The top is available in **stainless steel, granite or Zimbabwe black granite, with or without splashback** to suit your needs.

The refrigeration unit can be **mounted directly on the appliance, or connected remotely** for greater compactness and space management.

With **height-adjustable feet and optional wheels**, BLUE ROCK adapts perfectly to your workspace.




### GL version

Housed on the right only.




### GD version

Remote unit. Left or right control block.



### Splashback

Splashback with radiused rear edge.



### Finishes

Worktop in s/s, granite or black granite.

## Configuration examples



### BLUE ROCK 20

2 doors - ss panels  
granite top + splashback - remote unit



### BLUE ROCK 30

3 doors - white PVC panels  
black granite top - built-in unit



### BLUE ROCK 50

5 doors - stainless steel panels  
s/s top + splashback - built-in unit

## TECHNICAL DATA



### 1 – Door

Pivot hinges maintained from 90° with door return on closing.

### 2 – Monobloc interior fittings

10 max. levels (55mm spacing) per door for 400x600mm panels. Can be dismantled without tools.

### 3 – Magnetic door seals

Black TPE.

### 4 – Handle

Handle concealed in the door.

### 5 – Electronic controller

Digital display.

### 6 – Insulation thickness

60 mm - 42kg/m<sup>3</sup> foam.

### 7 – Stainless steel feet

Height adjustable from 920 to 970mm (optional wheels).

## BUT ALSO...

- + Housing made of panels assembled with eccentric and centering hooks for easy assembly.
- + Static refrigeration with evaporator (ventilation optional).
- + Natural defrost or forced defrost cycle available.
- + Evaporation tray for defrost water.
- + Doors with butterfly opening for easy transfer of trays from one door to another. Reversible on site.
- + Granite insulated from cold compartments.
- + Battery protected by cataphoresis treatment.
- + R455A refrigerant.
- + H.T.A (High Ambient Temperature, +43°C) or remote unit.
- + Supplied with 7 pair of slide rails as standard.



DIMENSIONS AND DATA

BLUE ROCK 20 / 30 / 40 / 50 / 60

- not available    € paying option

|                                     | 20                             | 30               | 40               | 50               | 60               |
|-------------------------------------|--------------------------------|------------------|------------------|------------------|------------------|
| Size of supports                    | 400x600 mm                     |                  |                  |                  |                  |
| Support entry direction             | 400 mm                         |                  |                  |                  |                  |
| Number of doors                     | 2                              | 3                | 4                | 5                | 6                |
| Max. number of levels per door      | 10 (spacing 5 mm)              |                  |                  |                  |                  |
| Standard number of levels per door  | 7                              |                  |                  |                  |                  |
| Number of supports per level        | 1                              |                  |                  |                  |                  |
| Level spacing                       | 55 mm                          |                  |                  |                  |                  |
| Adjustable every                    | 27,5 mm                        |                  |                  |                  |                  |
| Refrigerating unit                  | 1 unit of 1/3 Hp               | 1 unit of 1/3 Hp | 1 unit of 3/8 Hp | 1 unit of 3/8 Hp | 1 unit of 3/8 Hp |
| Refrigerating power at -10°C        | 0,6 kW                         | 0,6 kW           | 0,74 kW          | 0,74 kW          | 0,74 kW          |
| Fluid                               | R455A                          | R455A            | R455A            | R455A            | R455A            |
| Dimensions (LxPxH mm) - GL version* | 1435x885x917                   | 1965x885x917     | 2495x885x917     | 3025x885x917     | -                |
| Dimensions (LxPxH mm) - GD version* | 1270x885x917                   | 1800x885x917     | 2330x885x917     | 2860x885x917     | 3390x885x917     |
| Weight                              | 250 kg                         | 350 kg           | 450 kg           | 550 kg           | 550 kg           |
| Electrical supply                   | 220-240V / MONO ~1PH+N+T /50Hz |                  |                  |                  |                  |
| Power                               | 1 kW                           | 1 kW             | 1 kW             | 1 kW             | 1 kW             |
| Rated current                       | 4 A                            | 4 A              | 4 A              | 4 A              | 4 A              |

\*for feet, 150mm high (height of feet adjustable from 150 to 200 mm).

|   | OPTIONS |
|---|---------|
| Stainless Steel/granite/black granite top | €       |
| Splashback                                | €       |
| Ventilation                               | €       |
| Wheels                                    | €       |
| Additional pair of slide rails            | €       |

NON CONTRACTUAL DATA





# ALWAYS EVER- LASTING GOODS



Rue Benoit Frachon, 26800 PORTES-LES-VALENCE (France)  
Phone : +33 (0) 475 575 500 - Email : [contact@sebp-cfi.fr](mailto:contact@sebp-cfi.fr)  
[www.froid-cfi.fr](http://www.froid-cfi.fr) - [www.pavailer.com](http://www.pavailer.com)

---

an Ali Group Company



The Spirit of Excellence